

5K Submersible Pump Units

Description

The highly efficient hydraulic submersible pump is driven by a diesel engine to pump water at a rate of 5,000 gpm (18,927 Lpm) from a water source.

The pump is available as either a standalone pumping system to feed a standalone boost pump, or as a pump combination with a US Fire Pump Boost Pump. In either configuration, the water can be fed into large volume firefighting monitors such as the US Fire Pump Sentry 9[®] trailer mounted monitor, or sent over a long distance hose relay.

The submersible unit is compact and easy to deploy. The self-contained pumping system can be built on a base skid, a hook lift skid, or a trailer for easy transportation. A large integrated fuel tank can hold enough fuel to run the pump for up to 8 hours.

Firefighting experience and commitment to reliability are incorporated into the design of the control system. All US Fire Pump Submersible Pumps and submersible/boost combination units provide a user-friendly, water resistant control panel as a primary interface. Advanced sensors, redundant control mechanisms, and emergency shut-down switches are integrated for safe and easy operation.

The standalone submersible pump is ideal if you already have a US Fire Pump draft/boost pump. Weighing only 400 lbs. (181 kg), the floating unit is equipped with ergonomically designed carry handles, which allow operators to carry the pump unit into hard-to-reach locations. The combination of our submersible pump and our boost pump provides unparalleled pumping and boosting capabilities in one transportable package. An optional wireless controlled crane is also available to aid deployment of the floating unit.



US Fire Pump provides various options and customizations, such as noise attenuating enclosures, solar charging, intake and discharging manifolds, varying transport modes, emergency and scene lighting, and on-board crane options.

Features

- Reliable, heavy-duty components
- Fast, single person deployment
- Compact design
- Storz connections
- Scene lighting
- Powered rewind reel with 150ft hydraulic hose capacity
- Quick disconnects on hydraulic hose

Build Options

- Trailer mounted skid with hose storage and drop gate
- Hooklift enclosed skid with removable doors
- Weather resistant enclosure
- Sound attenuated enclosure
- Programmable engine controller

24 HOUR EMERGENCY RESPONSE: (225) 209 – 6551

Post Office Box 1810, Albany, LA 70711

Email: info@usfirepump.com www.usfirepump.com

Technical Specifications

| | |
|---|--|
| Model | Sub50 – Skid Mounted Hydraulic Submersible Pump Module |
| Base Material | Carbon Steel |
| Dimensions (LxWxH)⁵ | 224"x90"x115" (570cm x 230cm x 295cm) |
| Approximate Weight | 14,000 lbs. (6350 kg) |
| Standard Platform | Skid style template: Skid offers pick-and-place flexibility, and fits all US Fire Pump trailer layout options. |
| Pump Model | H50 floating submersible |
| Pump Type | Centrifugal End Suction |
| Pump Material | Standard option is epoxy coated cast Aluminum with Stainless Steel impellor |
| Drivers Available | CATERPILLAR, CUMMINS, JOHN DEERE, SCANIA, PERKINS |
| Fuel Cell Capacity | 60 gallons. Fuel cell sized proportionately to the engine size and hourly consumption. |
| Fuel Type | Diesel |
| Submersible Pump Discharge Outlet | 12" Storz Outlet Other options available |
| Control Panel | Simple engine control panel with LCD display for engine data and waterproof control switches for hydraulic pumps and accessories |
| Available Transportation Modes² | Gooseneck with 2 5/16 in. ball hitch (59 mm) or 2 in. King Pin (51 mm); or bumper pull trailer with 2 5/16 in. ball hitch (59 mm) or lunette eye / Pintle Hook |
| Maximum run time with full fuel tank | 8 hours per tank of fuel |
| Maximum Vertical Lift | 50ft (15 m) at 5,000 gpm ⁴ |
| Nominal Flow Rate | 5,000gpm |
| Maximum Ambient Temperature | 120° F (60° C) |
| Emission | EPA & CARB Tier IV, III & II (varies with model/options) |
| Protection System | Automatic alarm logging. Emergency kill switch. Auxiliary circuit breaker bank |

Note: Specifications are for reference only and subject to change without prior notice.

Specifications vary depending on configurations and options.

Send inquiries to US Fire Pump for details.

¹Other transportation modes include various trailers and skids.

²Some configurations may be weight limited.

³With both submersible pumps running.

⁴Pump Curves and additional information available upon request.

⁵Dimensions are subject to change depending on model and configuration

24 HOUR EMERGENCY RESPONSE: (225) 209 – 6551

Post Office Box 1810, Albany, LA 70711

Email: info@usfirepump.com www.usfirepump.com