



# 3% x 6% VSP

## FIRE FIGHTING & VAPOR SUPPRESSANT PRODUCT

## MULTIPURPOSE FLUORINE-FREE FOAM CONCENTRATE



### FAST FACTS

- UL-Listed fluorine-free foam for both hydrocarbon and polar solvent (water miscible) fuels
- UL 162 Listed
- Biodegradable and non-persistent
- Fresh, salt & brackish water compatible
- Fast knockdown & extinguishing performance
- Excellent burnback performance
- Great foam stability to extend drain time
- Compatible with multiple equipment systems



### DESCRIPTION

**Introducing the newly listed, but proven VSP 3x6 AR-SFFF:  
The Latest Innovation in Class B Firefighting Technology**

We are excited to unveil our newly listed UL162 Class B firefighting foam, engineered to tackle the toughest fires involving flammable liquids, polar solvents, and chemicals. Designed with cutting-edge technology and tested to the highest standards, VSP 3x6 is set to revolutionize how we approach fire suppression in industries such as aviation, oil & gas, marine, and chemical storage. The VSP product was developed in 2018 as a non-fluorinated vapor suppression product that has multiple proven applications and has been used over the years in actual incidents for post extinguishment vapor suppression. More than 80% of the foam utilized is on vapor suppression, not the actual extinguishment. The same long-lasting formulation reduces the number of applications needed to maintain the foam blanket for up to 2 hours.

### APPLICATIONS

- **Superior Suppression Power:** VSP 3x6 AR-SFFF forms a robust, long-lasting foam blanket that quickly smothers fires, preventing re-ignition and minimizing damage.
- **Fast-Acting & Effective:** The foam is formulated to deliver fast knockdown of Class B fires, reducing response times and enhancing firefighter safety.
- **Eco-Friendly Non-Fluorinated Formula:** Developed with sustainability in mind VSP 3x6 offers a composition that reduces environmental impact, containing no intentionally added fluorinated materials while maintaining high-performance standards.
- **Low Expansion & High Stability:** The foam creates a low expansion ratio for precision application, and its high stability ensures it withstands harsh conditions. The same proven, long-lasting blanket technology for vapor suppression is now UL Listed as a fire suppression product.
- **Compatibility:** It is compatible with current foam hardware.

### CERTIFICATIONS

Signature Series VSP 3x6

- UL 162 Listed
- **Packaging -**  
5 gallon pail  
55 gallon drum  
265 gallon tote

### FOAM PROPERTIES

	3%	6%
Dilution Rate	3%	6%
Foam Expansion Index	5 - 8	5 - 8
Drain Time	>60 minutes	>120 minutes



**ENVIRONMENTAL INFORMATION** US FIRE PUMP foam concentrates do not contain intentionally added PFAS chemicals including PFOA and PFOS. In making this statement, US Fire Pump and Perimeter Solutions rely on information provided by its raw material suppliers and certain independent laboratory analysis conducted on the product.

**NOTICE** Although the information and recommendations set forth herein (hereinafter "information") are presented in good faith and believed to be correct as of the date hereof, US FIRE PUMP and its affiliates make no representations or warranties as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving same will make their own determination as to its suitability for their purposes prior to use. In no event will US FIRE PUMP be responsible for damages of any nature whatsoever resulting from the use of, or reliance upon information or the product to which the information refers. Nothing contained herein is to be construed as a recommendation to use any product, process, equipment or formulation in conflict with any patent, and US FIRE PUMP makes no representation or warranty, express or implied, that the use thereof will not infringe any patent. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS.

**FOR MORE INFORMATION VISIT [WWW.USFIREPUMP.COM](http://WWW.USFIREPUMP.COM)**

US FIRE PUMP COMPANY, LLC  
27995 James Chapel Road North, Holden, LA 70744  
MAILING: PO Box 1810, Albany, LA 70711

**EMERGENCY 24 HOUR RESPONSE: (225) 209-6551**



USFP-202503-5