

3K Sub-Boost Pod

Description


The highly efficient hydraulic Sub-Boost pump is driven by a market leading diesel engine to pump water at a rate of 3000 gpm (11,350 Lpm). The use of our hydraulically driven submersible pump aids the mechanically driven pump by creating positive pressure, thus increasing efficiency of the system.

In either configuration, the water can be fed into large volume firefighting monitors such as the US Fire Pump Sentry 9[®] trailer mounted monitor, or sent over a long distance hose relay, substantially increasing the logistical efficiency at incident sites.

The submersible unit is compact and easy to deploy. The self-contained pumping system can be built on a base skid, a hook lift skid, or a trailer for easy transportation. A large integrated fuel tank can hold enough fuel to run the pump for up to 8 hours.

Firefighting experience and commitment to reliability are incorporated into the design of the control system. All US Fire Pump Submersible Pumps and submersible/boost combination units provide a user-friendly, water resistant control panel as a primary interface. Advanced sensors, redundant control mechanisms, and emergency shut-down switches are integrated for safe and easy operation.

The standalone submersible pump is ideal if you already have a US Fire Pump draft/boost pump. Weighing only 300 lbs. (136 kg), the floating unit is equipped with ergonomically designed carry poles which allow two or four operators to carry the pump unit into hard to reach locations. The combo pump provides unparalleled pumping and boosting capabilities in one transportable package.



US Fire Pump provides various options and customizations, such as noise attenuating enclosures, solar charging, intake and discharging manifolds, varying transport modes, emergency and scene lighting, and on-board crane options.

Features

- Reliable, heavy-duty components
- Fast, single person deployment
- Compact design
- Storz connections
- Scene lighting
- Powered rewind reel with 75ft hydraulic hose capacity
- Quick disconnects on hydraulic hose

Build Options

- Trailer mounted skid with hose storage and drop gate
- Hooklift enclosed skid with removable doors
- Weather resistant enclosure
- Sound attenuated enclosure
- Programmable engine controller

FOR MORE INFORMATION VISIT WWW.USFIREPUMP.COM

US FIRE PUMP COMPANY, LLC
 27995 James Chapel Road North, Holden, LA 70744
 MAILING: PO Box 1810, Albany, LA 70711

EMERGENCY 24 HOUR RESPONSE: (225) 209-6551



USFP-202503-6

Technical Specifications

Model	3K Sub-Boost Pod
Base Material	Carbon Steel
Dimensions (LxWxH)⁵	160x50x72" (406cm x 127cm x 182cm)
Approximate Weight	13,000 lbs. (5,900kg)
Standard Platform	Skid style template: Skid offers pick-and-place flexibility, and fits all US Fire Pump trailer layout options. ²
Pump Model	(1) 3000 GPM floating submersible (1) LFD 1000-2
Pump Type	Centrifugal End Suction
Pump Material	Standard option is epoxy coated cast Aluminum with Stainless Steel impellor
Drivers Available	CATERPILLAR, CUMMINS, JOHN DEERE, SCANIA, PERKINS
Fuel Cell Capacity	50 gallons. Fuel cell sized proportionately to the engine size and hourly consumption.
Fuel Type	Diesel
Submersible Pump Discharge Outlet	6" Storz Outlet Other options available
Control Panel	Simple engine control panel with LCD display for engine data and waterproof control switches for hydraulic pumps and accessories
Available Transportation Modes²	Hook-loader skid, gooseneck with 2 5/16 in. ball hitch (59 mm) or 2 in. King Pin (51 mm); or bumper pull trailer with 2 5/16 in. ball hitch (59 mm) or lunette eye / Pintle Hook
Maximum Run Time with Full Fuel Tank	8 hours per tank of fuel
Nominal Flow Rate	3000 gpm ³ (11,350 Lpm)
Maximum Ambient Temperature	120° F (60° C)
Emission	EPA & CARB Tier IV, III & II (varies with model/options)
Protection System	Automatic alarm logging. Emergency kill switch. Auxiliary circuit breaker bank

Note: Specifications are for reference only and subject to change without prior notice.

Specifications vary depending on configurations and options.

Send inquiries to US Fire Pump for details.

¹Other transportation modes include various trailers and skids.

²Some configurations may be weight limited.

³With both submersible pumps running.

⁴Pump Curves and additional information available upon request.

⁵Dimensions are subject to change depending on model and configuration

NOTICE Although the information and recommendations set forth herein (hereinafter "information") are presented in good faith and believed to be correct as of the date hereof, US FIRE PUMP and its affiliates makes no representations or warranties as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving same will make their own determination as to its suitability for their purposes prior to use. In no event will US FIRE PUMP be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information or the product to which the information refers. Nothing contained herein is to be construed as a recommendation to use any product, process, equipment or formulation in conflict with any patent, and US FIRE PUMP makes no representation or warranty, express or implied, that the use thereof will not infringe any patent. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS.

FOR MORE INFORMATION VISIT WWW.USFIREPUMP.COM

US FIRE PUMP COMPANY, LLC
27995 James Chapel Road North, Holden, LA 70744
MAILING: PO Box 1810, Albany, LA 70711

EMERGENCY 24 HOUR RESPONSE: (225) 209-6551



USFP-202503-6